


CHROME PLATED LONG LEVER QUICK ACTION HANDLE BASIN PILLAR TAP (For ambulant/handicapped toilet)




COMPLY WITH BSEN200:2008
BSEN248:2002
AS/NZS4020:2005
SS375: PART 1



PUB

CHARACTERISTIC

- Suitable for public, commercial and institutional washrooms.
- Saves water through built-in volume control.
- · Corrosion-resistant material.
- Easy installation and maintenance.



COMPONENT PARTS

| ITEM | PARTS | MATERIAL | | | | |
|------|----------------|--------------------------|--|--|--|--|
| 1. | Inlet Pipe | DZR Brass | | | | |
| 2. | Nut | Brass | | | | |
| 3. | Washers | NBR | | | | |
| 4. | Body | DZR Brass | | | | |
| 5. | Piston | DZR Brass, EPDM, Ceramic | | | | |
| 6. | Handle | Kirsite | | | | |
| 7. | Head Screw | Brass | | | | |
| 8. | Tab | ABS | | | | |
| 9. | Bubbler | Brass, POM, EPDM | | | | |
| 7. | Head Screw Tab | Brass ABS | | | | |

STANDARD SPECIFICATIONS

| SKU | APPLICABLE WATER PRESSURE | WATER TEMPERATURE | ENVIRONMENTA L TEMPERATURE | H (mm) | WATER SUPPLYING CALIBER | WEIGHT (kg) | PCS/CTN |
|--------|---------------------------------|----------------------|-------------------------------|-----------|-------------------------------|----------------|---------|
| NML8XL | 1.0Mpa | t ≤ 90°C | Room Temperature | 95 | 1/2" BSP | 0.520 | 30 |