


## OIL FILLED PRESSURE GAUGE (MODEL:WT-8001)








**RINSED** 

\*Calibration certificates are provided upon customer request (Additional added cost will be included)

FRONT VIEW

COMPONENT PARTS							
ITEM	PARTS	MATERIAL					
1	Case	Steel					
2	Viewing Lens	ABS					
3	Screw	Stainless Steel					
4	Socket	Brass					
5	Indicator Needle	Aluminium Black Painted					
6	Dial	Aluminium White painted with Black/ Red marking					
7	Stop Pin	Aluminium					
8	Oil	Glycerin					



## STANDARD SPECIFICATIONS

SKU	SIZE(mm)	L(mm)	W(mm)	H1(mm)	H2(mm)	Е	PCS/CTN	OPERATING PRESSURE
PG0503000F	50	52	27	71	51	1/4"BSPT	100	
PG0653000F	65	62	28.2	81	60.8	1/4"BSPT	50	0-300Psi kg/cm² 20bar
PG0803000F	80	81	32	112	80	3/8"BSPT	70	0-300FSI KG/CIII- ZUDAI
PG1003000F	100	109	37	136.6	99	1/2"BSPT	40	
PG1003500F	100	109	37	136.6	99	1/2"BSPT	40	0-350Psi kg/cm² 25bar

<sup>\*</sup> When releasing of pressure, please open release valve slowly to avoid pin out of calibration.