



SS213/SS272 uPVC PIPES

COMPLY WITH BS5255, BS4660









CROSS SECTIONAL VIEW

STANDARD SPECIFICATIONS

Pipe Standard	SS213:1983	SS272:2012		
Standard Length	5.8 meters			
Standard Color	White (SS213), Golden Brown (SS272)			
Material	uPVC			

FLUID AND APPLICATIONS

SS213 PIPES: Commonly used for sanitation application and are used in apartments, industrial & commercial buildings. It is also suitable for application such as rainwater down pipes and for other water discharge purposes.

SS272 PIPES: Commonly laid underground as sewer or
subsoil drainage for parks and fields. The golden brown gloss finish fabricated color reduces heat absorptions.

DIMENSIONS

SS213:1983 BS5255:1989

		- , ,	_ , ,			
SKU	DN (mm)	D (mm)	T (mm)	L (mm)	WEIGHT (kg)	
PIP213035	35	36.2-36.5	2.1-2.4	5800	2	
PIP213042	42	42.8-43.1	2.3-2.6	5800	3	
PIP213050	50	55.7-56.0	2.4-2.7	5800	4	
PIP213080	80	82.3-82.7	3.0-3.5	5800	7	
PIP213100	100	110.0-110.4	3.2-3.6	5800	10	
PIP213150	150	160.0-160.5	4.0-4.5	5800	18	
SS272:1983 BS4660:2000						
PIP272100	100	110.0-110.4	3.2-3.6	5800	10	
PIP272150	150	160.0-160.5	4.0-4.5	5800	18	